

Reppos

PUMPS

ΣΤΡΟΒΙΛΟΦΟΡΕΣ ΥΔΡΟΛΙΠΑΝΤΕΣ ΑΝΤΛΙΕΣ 6" 1450rpm/min

VERTICAL PUMPS 6" 1450rpm/min

ΤΥΠΟΣ TYPE	ΙΣΧΥΣ POWER		Α 380	ΠΑΡΟΧΗ ΣΕ m ³ /h (κ.μ/ω) CAPACITY								
	HP	KW		10	15	20	25	30	35	40	45	50
				ΜΑΝΟΜΕΤΡΙΚΟ ΥΨΟΣ ΣΕ ΜΕΤΡΑ-MANOMETRIC HEAD								
K14-07	5,5	4	6	17	16	15	14	13	11	8	7	4
K14-09	5,5	4	7,5	22	21	19	18	17	14	10	9	5
K14-12	7,5	5,5	10,3	29	27	26	24	22	19	14	12	7
K14-14	10	7,5	12	34	32	30	28	26	22	16	14	8
K14-16	10	7,5	13,7	39	37	34	32	30	25	18	16	9
K14-18	10	7,5	15,4	44	41	39	36	33	28	21	18	10
K14-20	12,5	9,2	17,1	49	46	43	40	37	31	23	20	11
K14-22	12,5	9,2	18,8	53	50	47	44	41	35	25	22	13
K14-24	15	11	20,5	58	55	51	48	45	38	27	24	14
K14-26	15	11	22,2	63	60	56	52	48	41	30	26	15
K14-28	17,5	13	24	68	64	60	56	52	44	32	28	16
K14-30	17,5	13	25,7	73	69	64	60	56	47	34	30	17
K14-32	20	15	27,4	78	73	68	64	60	50	36	32	18
K14-34	20	15	29,1	83	78	73	68	63	53	39	34	19
K14-36	25	18,5	30,8	87	82	77	72	67	57	41	36	21

ΤΥΠΟΣ TYPE	ΥΨΟΣ-HEIGHT mm	ΒΑΡΟΣ- WEIGHT kg
K14-07	1220	77,35
K14-09	1508	97,09
K14-12	1940	126,7
K14-14	2228	146,44
K14-16	2516	166,18
K14-18	2804	185,92
K14-20	3092	205,66
K14-22	3380	225,4
K14-24	3668	245,14
K14-26	3956	264,88
K14-28	4244	284,62
K14-30	4532	304,36
K14-32	4820	324,1
K14-34	5108	343,84
K14-36	5396	363,58

ΠΑΡΟΧΗ m ³ /h	ΣΩΛΗΝΑΣ ΚΑΤΑΘΛΙΨΗΣ	ΑΞΟΝΑΣ	ΒΑΘΟΣ ΤΟΠΟ/ΣΗΣ	ΚΕΦΑΛΗ
30	2 1/2"	3/4"	40	2 1/2"X3"
45	3"	7/8"	70	3"X3"
45	3"	1"	150	3"X4"
65	4"	1"	150	4"X5"

Reppos

PUMPS

ΣΤΡΟΒΙΛΟΦΟΡΕΣ ΥΔΡΟΛΙΠΑΝΤΕΣ ΑΝΤΛΙΕΣ 6" 1950rpm/min

VERTICAL PUMPS 6" 1950rpm/min

ΤΥΠΟΣ TYPE	ΙΣΧΥΣ POWER		Α 380	ΠΑΡΟΧΗ ΣΕ m ³ /h (κ.μ/ω) CAPACITY								
	HP	KW		20	25	30	35	40	45	50	55	60
				ΜΑΝΟΜΕΤΡΙΚΟ ΥΨΟΣ ΣΕ ΜΕΤΡΑ-MANOMETRIC HEAD								
K14-07	10	7,5	12	31	30	29	28	27	29	19	15	10
K14-09	10	7,5	15	40	39	37	36	35	30	24	19	13
K14-12	15	11	20,3	53	51	50	48	46	39	33	26	17
K14-14	15	11	23,3	62	60	58	56	54	46	38	30	20
K14-16	20	15	27	71	69	66	64	62	53	43	34	23
K14-18	20	15	30	80	77	75	72	69	59	49	39	26
K14-20	25	18,5	33	89	86	83	80	77	66	54	43	29
K14-22	25	18,5	36,8	97	94	91	88	85	72	60	47	31
K14-24	30	22	39,8	106	103	99	96	93	79	65	51	34
K14-26	30	22	43,5	115	112	108	104	100	86	70	56	37
K14-28	35	26	46,5	124	120	116	112	108	92	76	60	40
K14-30	35	26	49,5	133	129	124	120	116	99	81	64	43
K14-32	35	26	53,3	142	137	132	128	124	105	87	68	46
K14-34	40	30	56,3	151	146	141	136	131	112	92	73	49
K14-36	40	30	60	159	154	149	144	139	118	98	77	51

ΤΥΠΟΣ TYPE	ΥΨΟΣ-HEIGHT mm	ΒΑΡΟΣ- WEIGHT kg
K14-07	1220	77,35
K14-09	1508	97,09
K14-12	1940	126,7
K14-14	2228	146,44
K14-16	2516	166,18
K14-18	2804	185,92
K14-20	3092	205,66
K14-22	3380	225,4
K14-24	3668	245,14
K14-26	3956	264,88
K14-28	4244	284,62
K14-30	4532	304,36
K14-32	4820	324,1
K14-34	5108	343,84
K14-36	5396	363,58

ΠΑΡΟΧΗ m ³ /h	ΣΩΛΗΝΑΣ ΚΑΤΑΘΛΙΨΗΣ	ΑΞΟΝΑΣ	ΒΑΘΟΣ ΤΟΠΟ/ΣΗΣ	ΚΕΦΑΛΗ
30	2 1/2"	3/4"	40	2 1/2"X3"
45	3"	7/8"	70	3"X3"
45	3"	1"	150	3"X4"
65	4"	1"	150	4"X5"

ΤΥΠΟΣ TYPE	ΙΣΧΥΣ POWER		Α 380	ΠΑΡΟΧΗ ΣΕ m ³ /h (κ.μ/ω) CAPACITY											
				15	20	25	30	35	40	45	50	55	60	65	70
	HP	KW		ΜΑΝΟΜΕΤΡΙΚΟ ΥΨΟΣ ΣΕ ΜΕΤΡΑ-MANOMETRIC HEAD											
K14S-07	12,5	9,2	15,8	42	41	40	39	38	37	35	31	27	22	17	11
K14S-09	15	11	30,3	54	53	51	50	49	48	45	40	35	28	22	14
K14S-12	20	15	27	72	70	69	67	65	63	60	53	46	38	29	19
K14S-14	25	18,5	31,5	84	82	80	78	76	74	70	62	54	44	34	22
K14S-16	25	18,5	36	96	94	91	89	87	85	80	71	62	50	39	25
K14S-18	30	22	40,5	108	105	103	100	98	95	90	80	69	57	44	28
K14S-20	30	22	45	120	117	114	111	109	106	100	89	77	63	49	31
K14S-22	35	26	49,5	132	129	126	123	119	116	110	97	85	69	53	35
K14S-24	40	30	54	144	141	137	134	130	127	120	106	93	75	58	38
K14S-26	40	30	58,5	156	152	148	145	141	138	130	115	100	82	63	41
K14S-28	50	37	63	168	164	160	156	152	148	140	124	108	88	68	44
K14S-30	50	37	67,5	180	176	171	167	163	159	150	133	116	94	73	47
K14S-32	50	37	72	192	188	183	178	174	169	160	142	124	100	78	50
K14S-34	50	37	76,5	204	199	194	189	185	180	170	151	131	107	83	53
K14S-36	60	45	81	216	211	206	201	195	190	180	159	139	113	87	57

ΤΥΠΟΣ TYPE	ΥΨΟΣ-HEIGHT mm	ΒΑΡΟΣ- WEIGHT kg
K14S-07	1364	87,22
K14S-09	1652	106,96
K14S-12	2084	136,57
K14S-14	2372	156,31
K14S-16	2660	176,05
K14S-18	2948	195,53
K14S-20	3236	215,53
K14S-22	3524	235,27
K14S-24	3812	255
K14S-26	4100	274,75
K14S-28	4388	294,49
K14S-30	4676	314,23
K14S-32	4964	333,97
K14S-34	5252	353,71
K14S-36	5540	373,45

ΠΑΡΟΧΗ m ³ /h	ΣΩΛΗΝΑΣ ΚΑΤΑΘΛΙΨΗΣ	ΑΞΟΝΑΣ	ΒΑΘΟΣ ΤΟΠΟ/ΣΗΣ	ΚΕΦΑΛΗ
30	2 1/2"	3/4"	40	2 1/2"X3"
45	3"	7/8"	70	3"X3"
45	3"	1"	150	3"X4"
65	4"	1"	150	4"X5"